

3285996

QUALITY SINCE 1924

GENERAL PURPOSE CFL CFL PARA TODO USO

SOFT WHITE

ENERGY-EFFICIENT BAJO CONSUMO

Non-dimmable

This light bulb is warranted to be free from defects in workmanship and material for 2 years (based on normal household use of 3 hours per day). If it fails to do so, please call Toll Free 866-326-BULB for instructions on bulb replacement. This replacement is the sole remedy available and liability for incidental or consequential damage is expressly excluded. Do not return the bulb to the store.

* 9.1 year life based on rated life at 3 hours consumer use per day.

** Electricity cost savings based on using one 18 watt CFL for 10,000 hr rated life at 11c per kilowatt hour compared to ten 75 watt Soft White Incandescent Bulbs (rated life 1000 hrs).

** Ahorro en costos de energía al usar una bombilla fluorescente compacta de 18 vatios durante 10000 horas de vida nominal, a 11 centavos por kilovatio por hora, en comparación con 10 bombillas incandescentes de 75 vatios (1000 horas de vida nominal).

Lighting Facts

Brightness 1170 lumens Estimated Yearly \$2.17 nergy Cost
Based on 3 hrs/day,
11¢/kWh. Cost Energy Cost

depends on rates and use 9.1 years Based on 3 hrs/day

Light Appearance

visit epa.gov/cfl.

Energy Used 18 watts **Contains Mercury** For more on clean up and safe disposal,

A CAUTION

Risk of electric shock. Do not use where directly exposed to water. Do not open -Risk of electric shock. Up not use where directly exposed to water. Up not open-no user serviceable parts inside. Lamp may shatter and cause injury if broken. Remove and install by grasping only plastic portion of the lamp. Use only on 120 volt 60Hz circuits. Starting temperature -20F. Optimum operating temperature -10F to 140°F. Not for use in recessed fixtures. This device is not intended for use with emergency exit fixtures or emergency exit lights. Do not use with dimmers, photocontrols or electronic timers. Never use more than 25 lamps per 20 amp

A PRECAUCIONES

Peligro de choque eléctrico. No exponer directamente al agua. No abra este producto, ya que no contiene piezas reparables por el usuario. La lámpara puede astillarse y producir lesiones si se rompe. Sacarla o instalarla agarrándola solamente de la parte de plástico. Use solamente en circultus de 120 voltus 60 Hz. Temperatura inical 20°F. Operación optima de temperatura-10°F a 140°F. No debe utilizarse en accesorios empotrados. No use con accesorios de salida de emergencia, luces de emergencia. Luces de salida, reductor de luz, fotocontrol oh contador electrico. Nunca use mas de 25 lámparas por 20 amp de ramo circuito.

(Hg) - LAMP CONTAINS MERCURY

Dispose of accordingly to local, state and federal law. For details visit www.lamprecycle.org

LA LÁMPARA (Hg) CONTIENE MERCURIO

Por favor deseche de acuerdo a las leves locales. estatales y federales. Para más detailies, visite www.lamprecycle.org

e producto Ace, cuando se usa para entendidos, no funciona a su entera ucción, devuélvalo a la ferretería de la compara de la co

ESL18T2/5/ACE

